



## ACCUBRIDGE® 6020T AUTOMATED THERMOMETRY BRIDGE



### Featuring

- ▶ Multiple Display Modes Including:
  - ▶ Temperature (°C, K, °F)
  - ▶ Resistance,  $\Omega$
  - ▶ Ratio
- ▶ ADCC Technology
- ▶ Accu-T-Cal™ Software (NMI Designed)
- ▶ New Microcontroller
- ▶ New User Interface
- ▶ Two Models to select from

### Overview

The **AccuBridge® 6020T** Thermometry Bridge is the metrologist's choice for primary lab level thermometry measurements. With its innovative technology, the 6020T's speed, measurement accuracy, and data handling capabilities make it the preferred primary thermometry measurement system in National Measurement Institutes (NMIs) and other primary labs worldwide. The 6020T was designed for flexibility and ease of use. The 6020T features increased

ampere-turn (AT) sensitivity with more turns on both the master and slave windings and a voltage feedback circuit to improve the linearity error of the nanovolt amplifier. Also improved is the ratio from the previous 1.5:1 ratio to the new ratio range covering from 0.1 up to a maximum ratio of 14 allowing customers to meet all of their requirements. MI customers now have unmatched features and functionality to support 6020T's world-class measurement uncertainty capability.

Feature	Benefit
Best accuracy $\pm 0.015$ ppm from 1 $\Omega$ to 10 k $\Omega$ (equivalent accuracy of 0.004 mK at TPW <sup>1</sup> ).	Highest level of accuracy achievable in a commercial DCC bridge.
0.1 $\Omega$ to 100 k $\Omega$ range.	Widest range providing customers one bridge solution.
2-channel front panel scanner with keep warm currents.	Customers do not need to purchase an additional scanner.
Quick measure mode	Provides you with the ultimate response time for first measurement, less than 20 seconds.
Current reversal rate as low as 2 seconds.	Gives you world's quickest DC bridge current reversal time of 2 seconds.
Store calibration coefficients for up to 5 thermometers without software aide.	Allows internal memory storage for quick front-panel measurements.
NEW 6020T-P-LEMO model with Lemo connectors for RT and Rs connections (Optional)	Improves confidence in removal of errors due to thermals, drafts, external noise.



## ACCUBRIDGE® 6020T AUTOMATED THERMOMETRY BRIDGE

### Specifications: Rev 14

Model	6020T - Premium/6020T-P-LEMO	
Current Reversal Minimum (s)	2	
Sample Rate Minimum (s)	0.1	
R <sub>s</sub> value (Ω)	Accuracy of Ratio* (x 10 <sup>-6</sup> )	
	1:1	14:1
0.1 to < 1	0.015	0.015
1 to < 10	0.015	0.015
10 to < 100	0.015	0.015
100 to < 1 k	0.015	0.015
1 k to 10 k	0.015	0.015
10 k to < 100 k	N/A	0.2

  

Model	6020T - Standard	
Current Reversal Minimum (s)	2	
Sample Rate Minimum (s)	0.1	
R <sub>s</sub> value (Ω)	Accuracy of Ratio* (x 10 <sup>-6</sup> )	
	1:1	14:1
0.1 to < 1	0.07	0.07
1 to < 10	0.07	0.07
10 to < 100	0.07	0.07
100 to < 1 k	0.07	0.07
1 k to < 10 k	0.07	0.07
10 k to < 100 k	N/A	0.2

\*Ratio define as (R<sub>PRT</sub> / R<sub>s</sub>)

Based on a 25.5 Ω SPRT Using a 25 Ω Reference Resistor			Measurement Mode	4-wire
Temperature	Premium	Standard	Linearity	< 0.005 x 10 <sup>-6</sup> of full-scale
TPAr	0.001 mK	0.003 mK	Operating Conditions	10 °C to 35 °C, 10 % to 90 % RH non-condensing
TPW	0.004 mK	0.017 mK	Test Current Range	1 μA to 200 mA
FPSn	0.008 mK	0.035 mK	Test Current Resolution	18-bit
			Interface	IEEE-488
			Display	Touch-screen display (no external keyboard), resolution 0.001 x 10 <sup>-6</sup>

**Dimensions (L × W × H):**  
438 × 406 × 267 (mm)

**Weight:**  
21 kg

**Shipping Weight:**  
30 kg

**Mains Power:**  
100 V<sub>ac</sub> /120 V<sub>ac</sub> /220 V<sub>ac</sub> /240 V<sub>ac</sub>  
50/60 Hz

**Corporate Headquarters**  
Measurements International  
PO Box 2359, 118 Commerce Drive  
Prescott, Ontario, Canada K0E 1T0  
Phone: 613-925-5934  
Fax: 613-925-1195  
Email: sales@mintl.com  
Toll Free: 1-800-324-4988

