



9300A TEMPERATURE CONTROLLED AIR BATH



Featuring

- ▶ Volume 106 Litres
- ▶ Range $\pm 15\text{ }^{\circ}\text{C}$ to $40\text{ }^{\circ}\text{C}$
- ▶ Stability ± 0.005 @ $23\text{ }^{\circ}\text{C}$
- ▶ Peltier Cooled
- ▶ Fast Heating/Cooling Rate
- ▶ Stainless Steel Construction
- ▶ Perfect for Temperature Coefficient Measurements

Overview

The Model 9300A Series Temperature Controlled Chambers are designed as a convenient and inexpensive way to maintain the temperature of air resistors in the calibration laboratory. It is large enough to house several standard air resistors and features two adjustable shelves to permit easy access to the standards. The shelves are easily removable.

Easy access to the inside of the chamber is achieved through the conveniently mounted front door. Resistor leads are brought into the chamber through a small, insulated opening in the rear of the unit. The integrated control unit adds convenience as it eliminates a separate controller unit. Temperature control is located inside the

chamber. A keyboard control can be used to set the individual temperatures between $15\text{ }^{\circ}\text{C}$ and $40\text{ }^{\circ}\text{C}$, or the temperature may be set over the GPIB.

Cooling and heating for the chamber is provided for by a thermoelectric Peltier element using internal thermistors as sensing elements. Internal fans are used to move the air inside the chamber to provide for better temperature stability and uniformity while maintaining a quiet operation. The internal temperature is shown on an external display located on the front of the chamber.

The Over Temperature Protection (OTP) has 4 selectable ranges.

Feature	Benefit
Peltier Cooled	Does not suffer from the electric and audible noise of a compressor based airbath
GPIB Controlled	Allows for calculation of a α and β coefficients
Large Working Area	Allows to multiple resistance standards or product
Fast heating/cooling rate	Quickly recovers from open door
2 Level Temperature Protection	Prevents thermal runaway should Heater/Cooler fail
MI Software Compatible	Interfaces with existing MI Software for ease of integration



9300A TEMPERATURE CONTROLLED AIR BATH

Specifications: Rev 11

Internal Dimensions (LxWxH)	510 mm x 330 mm x 630 mm
Volume (L)	106
Temperature Range (°C)	+ 15 to + 40
Temperature Display Resolution (°C)	0.001
Temperature Set Resolution (°C)	0.001
Temperature Stability (°C)	± 0.005 @ 23 °C
Temperature Uniformity (°C)	± 0.01 @ 23 °C ± 0.05 @ 15 °C ± 0.10 @ 35 °C
Heating Rate	100 min (+ 15 °C to + 40 °C)
Cooling Rate	100 min (+ 40 °C to + 15 °C)
Temperature Control	PID
Interface	GPIB
Shelves	2
Access Port	1 x 50 mm Dia

Dimensions (L × W × H):
660 mm x 445 mm x 940 mm

Weight:
73 kg

Shipping Weight:
88 kg

Mains Power:
100 to 240 V_{ac}, 50/60 Hz, 300 VA

Corporate Headquarters
Measurements International
PO Box 2359, 118 Commerce Drive
Prescott, Ontario, Canada K0E 1T0
Phone: 613-925-5934
Fax: 613-925-1195
Email: sales@mintl.com
Toll Free: 1-800-324-4988

